



Cisco Prime Access Registrar 6.0.2 Release Notes

Cisco Prime Access Registrar (Prime Access Registrar) is a high performance, carrier class RADIUS/Diameter solution that provides scalable, flexible, intelligent authentication, authorization, and accounting (AAA) services.

Prime Access Registrar comprises a RADIUS/Diameter server designed from the ground up for performance, scalability, and extensibility for deployment in complex service provider environments including integration with external data stores and systems. Session and resource management tools track user sessions and allocate dynamic resources to support new subscriber service introductions.



Note

Prime Access Registrar can be used with Red Hat Enterprise Linux 5.3/5.4/5.5/6.0/6.1/6.2 32-bit /64-bit operating system (64-bit operating system can be used with the required 32-bit libraries installed) using kernel 2.6.18-128.el5 or later versions of 2.6, and Glibc version: glibc-2.5-34 or later.

Contents

This release note contains the following sections:

- [Enhanced Features in Cisco Prime Access Registrar 6.0.2, page 2](#)
- [System Requirements, page 3](#)
- [Co-Existence With Other Network Management Applications, page 3](#)
- [Known Anomalies in Cisco Prime Access Registrar 6.0.2.4, page 4](#)



- [Known Anomalies in Cisco Prime Access Registrar 6.0.2.3, page 4](#)
- [Known Anomalies in Cisco Prime Access Registrar 6.0.2.1, page 4](#)
- [Known Anomalies in Cisco Prime Access Registrar 6.0.2, page 4](#)
- [Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.4, page 5](#)
- [Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.3, page 5](#)
- [Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.2, page 5](#)
- [Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.1, page 6](#)
- [Anomalies Fixed in Cisco Prime Access Registrar 6.0.2, page 6](#)
- [Related Documentation, page 6](#)

Enhanced Features in Cisco Prime Access Registrar 6.0.2

Prime Access Registrar has the following enhancements for 6.0.2:

- [HLR GT Caching, page 2](#)
- [Support for Parallelization in SIGTRAN / M3UA Remote Servers, page 3](#)

HLR GT Caching

The Home Location Registry (HLR) Global Title address (GT address in calling party address (CgPA)) from the SendAuthenticationInfo (SAI) response is cached and used for subsequent authorization request. This cached HLR GT is added to the environment dictionary of the packet to be available for the authorization flow.

The following environment dictionary variables are added to hold the cached HLR GT:

- HLR-GlobalTitle-Cached—Set as TRUE to indicate the HLR GT is cached
- Cached-HLR-GlobalTitle-Digits
- Cached-HLR-Translation-Type
- Cached-HLR-Numbering-Plan
- Cached-HLR-Encoding-Scheme
- Cached-HLR-Nature-Of-Address
- Cached-HLR-GT-Format

The cached HLR GT overrides both the configured destination GT values and GT script provided GT values. The HLR GT caching works by default for RTE_GT. The cached HLR GT can be overridden by updating the environment variable HLR-GlobalTitle-Cached to FALSE (or anything other than TRUE) in the GT script.

The HLR GT will not be cached for:

- reauthentication flow
- authorize only flow, when authentication vectors are already available in cache, as SAI request will not be available.

Support for Parallelization in SIGTRAN / M3UA Remote Servers

Whenever Prime Access Registrar sends a packet to a remote server, it waits for a response from the remote server before sending further packets to the same or other remote servers (as configured). This causes performance impact. Prime Access Registrar 6.0.2 introduces a feature that allows multiple simultaneous outstanding requests to be sent to the same or other remote servers (as configured).

System Requirements

This section describes the system requirements to install and use the Prime Access Registrar software.

[Table 1](#) lists the system requirements for Prime Access Registrar 6.0.2.

Table 1 Minimum Hardware and Software Requirements for Prime Access Registrar Server

Component	Linux Operating System
OS version	RHEL 5.3/5.4/5.5/6.0/6.1/6.2
Model	X86
CPU type	Intel Xeon CPU 2.3 GHz
CPU Number	4
CPU speed	2.3 GHz
Memory (RAM)	8 GB
Swap space	10 GB
Disk space	1*146 GB



Note Solaris support for Prime Access Registrar 6.0.2 will be implemented in a future release.

Co-Existence With Other Network Management Applications

To achieve optimal performance, Prime Access Registrar should be the only application running on a given server. In certain cases, when you choose to run collaborative applications such as a SNMP agent, you must configure Prime Access Registrar to avoid UDP port conflicts. The most common conflicts occur when other applications also use ports 2785 and 2786. For more information on SNMP configuration, see the Configuring SNMP section, in the [Installing and Configuring Cisco Prime Access Registrar, 6.0](#).

Known Anomalies in Cisco Prime Access Registrar 6.0.2.4

Table 2 lists the known anomalies in Prime Access Registrar 6.0.2.4.

Table 2 Known Anomaly in Prime Access Registrar 6.0.2.4

Bug	Description
CSCuj71260	In Prime Access Registrar, add-example-configuration.rc script fails.
CSCun20370	Upgrade fails if default attributes are deleted in lower version.
CSCus55143	In Solaris, Prime Access Registrar does not work with external session manager.

Known Anomalies in Cisco Prime Access Registrar 6.0.2.3

Table 3 lists the known anomaly in Prime Access Registrar 6.0.2.3.

Table 3 Known Anomaly in Prime Access Registrar 6.0.2.3

Bug	Description
CSCus55143	In Solaris, Prime Access Registrar does not work with external session manager.

Known Anomalies in Cisco Prime Access Registrar 6.0.2.1

Table 4 lists the known anomaly in Prime Access Registrar 6.0.2.1.

Table 4 Known Anomaly in Prime Access Registrar 6.0.2.1

Bug	Description
CSCue75064	Send Authentication Info message should handle the user error.

Known Anomalies in Cisco Prime Access Registrar 6.0.2

Table 5 lists the known anomaly in Prime Access Registrar 6.0.2.

Table 5 Known Anomaly in Prime Access Registrar 6.0.2

Bug	Description
CSCue75064	Send Authentication Info message should handle the User error.

Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.4

Table 6 lists the anomalies fixed in Prime Access Registrar 6.0.2.4.

Table 6 *Anomalies Fixed in Prime Access Registrar 6.0.2.4*

Bug	Description
CSCut03384	Unable to launch GUI.
CSCus98217	In Prime Access Registrar, the "/Radius/Advanced" property values are not updated when changes are done through GUI.
CSCus98150	Getting unexpected message/symbol during installation.
CSCur96025	Prime Access Registrar 6.0 and 6.1 installation process fails with director license.

Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.3

Table 7 lists the anomalies fixed in Prime Access Registrar 6.0.2.3.

Table 7 *Anomalies Fixed in Prime Access Registrar 6.0.2.3*

Bug	Description
CSCud00132	Prime Access Registrar getting crashed after upgrade.
CSCug23495	Replication issues in Prime Access Registrar 6.0.1.
CSCuh11513	Prime Access Registrar crashes if ORACLE path is invalid or does not exist.
CSCul58044	Cannot configure OCI Oracle and ODBC MySQL RemoteServers at the same time.
CSCun80986	Unable to add two OCI remote servers with single ocisource.
CSCup94803	Oracle connection not released upon ungraceful shutdown.
CSCuq04537	CarSigtranLicenseUsage is sent continuously when SNMP trap is enabled.
CSCus41908	radiusAuthServerInetAddressType MIB object is missing in the SNMP trap.
CSCus41962	Maximum number of log files needs to be increased to 200.

Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.2

Table 8 lists the anomalies fixed in Prime Access Registrar 6.0.2.2.

Table 8 *Anomalies Fixed in Prime Access Registrar 6.0.2.2*

Bug	Description
CSCue75064	Send Authentication Info message should handle the User error.
CSCul73611	SIGTRAN-M3UA source GT digit (CgPA) length needs to support up to 15 digits.
CSCum47631	M3UA CLI client is getting crashed while logs roll over.
CSCun27477	MAP-RESTORE-DATA flow not working properly.

Anomalies Fixed in Cisco Prime Access Registrar 6.0.2.1

Table 9 lists the anomalies fixed in Prime Access Registrar 6.0.2.1.

Table 9 Anomalies Fixed in Prime Access Registrar 6.0.2.1

Bug	Description
CSCuI29176	Segmentation fault occurs in service with 6.0 base license in Prime Access Registrar 6.1.
CSCuI15395	Base license should not allow you to enable TACACS+ in Prime Access Registrar.
CSCuI32028	Prime Access Registrar crashes with eap-sim and sigtran-m3ua remote server during traffic.

Anomalies Fixed in Cisco Prime Access Registrar 6.0.2

Table 10 lists the anomalies fixed in Prime Access Registrar 6.0.2.

Table 10 Anomalies Fixed in Prime Access Registrar 6.0.2

Bug	Description
CSCuI03911	MAP request to support CgPA formatting to subsequent MAP requests in CdP.
CSCuI07108	Need validation for sigtran-m3ua multiple association/remote server.
CSCuI11853	Prime Access Registrar should send error log for OCI, while accessing the empty DB fields.
CSCuI24502	Rfc compliance for routing context mapping.
CSCuI26360	Need to set a limit/count of number of consecutive timeouts in sigtran-m3ua.
CSCuF80663	Parallelization needs to be supported in SIGTRAN M3UA remote server.

Related Documentation

The following is a list of the documentation for Prime Access Registrar 6.0.2. You can access the URLs listed for each document at www.cisco.com on the World Wide Web. We recommend that you refer to the documentation in the following order:

- [Cisco Prime Access Registrar 6.0.2 Release Notes](#)
- [Cisco Prime Access Registrar 6.0.1 User Guide](#)
- [Open Source Used In Cisco Prime Access Registrar 6.0.1](#)

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see *What's New in Cisco Product Documentation* at: <http://www.cisco.com/c/en/us/td/docs/general/whatsnew/whatsnew.html>.

Subscribe to *What's New in Cisco Product Documentation*, which lists all new and revised Cisco technical documentation as an RSS feed and delivers content directly to your desktop using a reader application. The RSS feeds are a free service.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2015 Cisco Systems, Inc. All rights reserved.

