



# Release Notes for Cisco Unified Survivable Remote Site Telephony, Release 14.2

---

**First Published: December 18, 2020**

**Last Updated: April 15, 2022**

## Contents

- [System Requirements, page 2](#)
- [New and Changed Information, page 4](#)
- [Caveats, page 4](#)
- [Related Documentation, page 4](#)
- [Service and Support, page 5](#)



# Introduction

This Release Notes document describes the features of Cisco Unified Survivable Remote Site Telephony, Release 14.2. The Cisco Unified Survivable Remote Site Telephony, Release 14.2 is included in Cisco IOS XE Cupertino 17.8.1a and later releases.

To ensure that you have the latest version of this Release Notes, go to <https://www.cisco.com/c/en/us/products/unified-communications/unified-survivable-remote-site-telephony/index.html>. Choose Release and General Information > Release Notes, and locate the latest release notes pertaining to your release.

## System Requirements

- [Hardware Supported, page 2](#)
- [Software Compatibility, page 3](#)
- [Determining the Software Version, page 3](#)
- [Upgrading to a New Software Release, page 3](#)
- [Feature Set Tables, page 3](#)

## Hardware Supported

### Platforms

Unified SRST supports the following Cisco 4000 Series Integrated Services Router platforms:

- Cisco 4321 Integrated Services Router
- Cisco 4331 Integrated Services Router
- Cisco 4351 Integrated Services Router
- Cisco 4431 Integrated Services Router
- Cisco 4451 Integrated Services Router
- Cisco 4461 Integrated Services Router

Unified SRST supports the following Cisco 8300 Catalyst Edge Series platforms:

- C8300-1N1S-6T
- C8300-1N1S-4T2X
- C8300-2N2S-6T
- C8300-2N2S-4T2X

Unified SRST supports the following Cisco 8200 Catalyst Edge Series platform:

- C8200-1N-4T

Unified SRST also supports the following Router platforms:

- Cisco 1100 Series Integrated Services Router
- C8200L-1N-4T

## Software Compatibility

For more information on supported images and minimum software version requirement for Unified SRST features, see *Cisco Unified SCCP and SIP SRST System Administrator Guide*.

To determine the correct Cisco IOS release to support a specific Unified SRST version, see the *Cisco Unified CME, Unified SRST, and Cisco IOS Software Version Compatibility Matrix*.

Use Cisco Feature Navigator to find information about platform support and Cisco IOS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. You do not need an account on Cisco.com for access.

## Determining the Software Version

To determine the release of Cisco IOS software currently running on your Cisco router, log in to the router and enter the **show version** command. The following sample output from the **show version** command indicates the Cisco IOS release on the first output line:

```
Router-4400# show version
Cisco IOS XE Software, Version Cisco IOS XE Cupertino 17.8.1a
Cisco IOS Software, ISR Software (X86_64_LINUX_IOSD-UNIVERSALK9-M),
Copyright (c) 1986-2022 by Cisco Systems, Inc.
Compiled Fri 7-Jan-22 01:12.
```

## Upgrading to a New Software Release

To determine which Cisco IOS software release supports the recommended Unified SRST version, see *Unified SRST and Cisco IOS Software Compatibility Matrix*. To install the new software release, see the “Install Cisco IOS Software” section of the *Cisco Unified Communications Manager Express Administrator Guide*.

## Feature Set Tables

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>.

# New and Changed Information

- [New Features in Unified SRST, Release 14.2, page 4.](#)

## New Features in Unified SRST, Release 14.2

- From Unified SRST Release 14.2, Unified SRST for SIP and SCCP may be configured to only allow SHA2 TLS1.2 ciphers. For more information, see [Cisco Unified SCCP and SIP SRST System Administrator Guide \(All Versions\)](#).
- From Unified SRST Release 14.2, SIP clients that use token-based authentication can register to Unified SRST during a WAN outage. For more information, see [Cisco Unified SCCP and SIP SRST System Administrator Guide \(All Versions\)](#).

## Caveats

- [Open Caveats—Unified SRST, Release 14.2, page 4](#)

## Open Caveats—Unified SRST, Release 14.2

There are no open or unresolved caveats for Unified SRST, 14.2 Release.

# Related Documentation

## Software Documents

### Administrator Guides

- [Cisco Unified Communications Manager Express System Administrator Guide](#)
- [Cisco Unified SCCP and SIP SRST System Administrator Guide \(All Versions\)](#)
- [Phone Feature Support Guide for Unified CME, Unified SRST, Unified E-SRST, and Unified Secure SRST](#)

### Command References

- [Cisco Unified Communications Manager Express Command Reference](#)
- [Cisco Unified SRST and Cisco Unified SIP SRST Command Reference \(All Versions\)](#)

### Release Notes

- [Release Notes for Cisco Unified Communications Manager Express](#)

# Service and Support

The Cisco Support and Documentation website provide online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies.

Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.

To access the website, go to: <http://www.cisco.com/cisco/web/support/index.html>.

## Obtain Documentation and Submit a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see [What's New in Cisco Product Documentation](#).

To receive new and revised Cisco technical content directly to your desktop, you can subscribe to the [What's New in Cisco Product Documentation RSS feed](#). The RSS feeds are a free service.

---

This document is to be used in conjunction with the documents listed in the “[Related Documentation](#)” section.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2022 Cisco Systems, Inc. All rights reserved.

